

The UK's largest independent multi-metals stockholder





Stainless Steel High Pressure Fittings

## Threaded Fittings









90° Elbow

45° Elbow

Equal Tee

Reducing Tee Hexagon Plug











Cap

Full Coupling

Half Coupling

Union

Hexagon Nipple

## Socket Weld Fittings









90° Elbow

45° Elbow

Equal Tee

Reducing Tee









Full Coupling

Union

Cap

The information contained herein is based on our present knowledge and experience and is given in good faith. However, no liability will be accepted by the Company in respect of any action taken by any third party in reliance thereon.

As the products detailed herein may be used for a wide variety of purposes and as the Company has no control over their use, the Company specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or their fitness for any particular purpose. Any advice given by the Company to any third party is given for that party's assistance only and without any liability on the part of the Company.

Any contract between the Company and a customer will be subject to the Company's Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available on request.

Dimensions: Please note that all dimensions are approximate and may vary according to manufacturing tolerances. (Issue 2 - March 2012)



# Stainless Steel High Pressure Fittings

To complement the already extensive stock range of Stainless Steel ANSI Pipe, Fittings and Flanges, Aalco now holds a range of ANSI B16.11 3000lb High Pressure Fittings.

The range includes 3000lb Socket Weld fittings and 3000lb NPT Threaded Fittings, both in grades 304L and 316L.

If you do not find what you require here, please call your local Service Centre, listed on the back cover, as the range is always expanding.

AALCO is a registered trademark of Aalco Metals Ltd



### 90° Elbow

### SOCKET WELDING - Dimensions in millimeters

	Nominal			С					Grades A	vailable
DN				(Min)	D					316L
15	1/2	21.8	4.67	4.09	15.8	15.5	3.73	9.5	1	✓
20	3/4	27.2	4.90	4.27	21.0	19.0	3.91	12.5	1	✓
25	1	33.9	5.69	4.98	26.7	22.5	4.55	12.5	1	✓
32	11/4	42.7	6.07	5.28	35.1	27.0	4.85	12.5	1	✓
40	1½	48.8	6.35	5.54	40.9	32.0	5.08	12.5	1	✓
50	2	61.2	6.93	6.04	52.5	38.0	5.54	16.0	1	1



### 45° Elbow

### SOCKET WEI DING - Dimensions in millimeters

	Nominal			С					Grades A	vailable
DN				(Min)	D					
15	1/2	21.8	4.67	4.09	15.8	11.0	3.73	9.5	1	-
20	3/4	27.2	4.90	4.27	21.0	13.0	3.91	12.5	1	-
25	1	33.9	5.69	4.98	26.7	14.0	4.55	12.5	1	1
40	1½	48.8	6.35	5.54	40.9	20.5	5.08	12.5	1	1
50	2	61.2	6.93	6.04	52.5	25.5	5.54	16.0	1	<b>/</b>





## **Equal Tee**


### SOCKET WEI DING - Dimensions in millimeters

	Nominal			С					Grades A	vailable
DN				(Min)	D					316L
15	1/2	21.8	4.67	4.09	15.8	15.5	3.73	9.5	1	-
20	3/4	27.2	4.90	4.27	21.0	19.0	3.91	12.5	✓	✓
25	1	33.9	5.69	4.98	26.7	22.5	4.55	12.5	1	✓
40	1½	48.8	6.35	5.54	40.9	32.0	5.08	12.5	1	✓
50	2	61.2	6.93	6.04	52.5	38.0	5.54	16.0	1	✓














## **Reducing Tees**


SOCK	KET WE	LDING	- Dime	nsions	in milli	meters									
Nom. P	ipe Size			Flo						Branch			Grades Available		
								C1							
Flow	Branch			(Min)	D			В1		(Min)	D1			316L	
3/4	1/2	27.2	4.90	4.27	21.0	19.0	3.91	21.8	4.01	3.5	15.8	9.5	-	✓	
1	1/2	33.9	5.69	4.98	26.7	22.5	4.55	21.8	4.01	3.5	15.8	9.5	<b>✓</b>	✓	
1	3/4	33.9	5.69	4.98	26.7	2.5	4.55	27.2	4.90	4.27	21.0	12.5	✓	✓	
1½	1/2	48.8	6.35	5.54	40.9	32.0	5.08	21.8	4.01	3.5	15.8	9.5	1	✓	
1½	3/4	48.8	6.35	5.54	40.9	32.0	5.08	27.2	4.90	4.27	21.0	12.5	1	1	
1½	1	48.8	6.35	5.54	40.9	32.0	5.08	33.9	5.69	4.98	26.7	12.5	-	1	
2	1/2	61.2	6.93	6.04	52.5	38.0	5.54	21.8	4.01	3.5	15.8	9.5	1	✓	
2	3/4	61.2	6.93	6.04	52.5	38.0	5.54	27.2	4.90	4.27	21.0	12.5	1	1	
2	1	61.2	6.93	6.04	52.5	38.0	5.54	33.9	5.69	4.98	26.7	12.5	1	1	
2	1½	61.2	6.93	6.04	52.5	38.0	5.54	48.8	6.35	5.54	40.9	12.5	-	✓	



## Full Coupling

SOCKET W	/ELDING - D	imensions	in millimete	ers					
	Nominal							Grades .	Available
DN				(Min)	D				316L
15	1/2	21.8	4.67	4.09	15.8	9.5	9.5	✓	1
20	3/4	27.2	4.90	4.27	21.0	9.5	12.5	1	1
25	1	33.9	5.69	4.98	26.7	12.5	12.5	✓	1
32	11/4	42.7	6.07	5.28	35.1	12.5	12.5	1	-
40	1½	48.8	6.35	5.54	40.9	12.5	12.5	✓	/
50	2	61.2	6.93	6.04	52.5	19.0	16.0	1	1







### Union

### SOCKET WELDING - Dimensions in millimeters

Nom.	Pipe End	Socket Bore	Socket Wall	Water Way	Laying Lngth	Male Flange		Thrds / 25.4mm	Bearing (min) J	Socket Depth	Length Assem.	Clear Assem.	Grades A	wailable
Pipe Size						(min) F		25.411111						316L
1/2	31.2	22.23 21.72	4.09	16.56 15.04	26.9 20.6	3.68	3.68	14	1.50	9.7	49.0	58.4	-	1
3/4	37.1	27.56 27.05	4.27	21.69 20.17	31.8 25.4	4.06	4.06	11	1.68	12.7	56.9	66.0	1	1
1	45.5	34.29 33.78	4.98	27.41 25.88	34.3 26.2	4.57	4.45	11	1.85	12.7	62.0	78.7	1	1
1½	61.5	49.15 48.64	5.54	41.66 40.13	42.2 34.0	5.84	5.59	10	2.31	12.7	76.5	111.8	1	1
2	75.2	61.62 61.11	6.05	53.26 51.74	45.6 37.3	6.60	6.35	10	2.69	15.7	86.1	132.1	✓	1



### 90° Elbow

### THREADED - Dimensions in millimeters

	Nominal	Length of T	Length of Thread (min)				Grades A	Available
DN								316L
15	1/2	10.9	13.6	25	4.09	38	✓	✓
20	3/4	12.7	13.9	28	4.32	46	✓	✓
25	1	14.7	17.3	33	4.98	56	✓	✓
32	11/4	17.0	18.0	51	5.28	62	1	✓
40	1½	17.8	18.4	60	5.56	75	✓	1
50	2	19.0	19.2	64	7.14	84	<b>√</b>	<b>√</b>





### 45° Elbow


### THREADED - Dimensions in millimeters

	Nominal	Length of T	hread (min)				Grades A	Available
DN								
15	1/2	10.9	13.6	25	4.09	38	✓	-
20	3/4	12.7	13.9	28	4.32	46	✓	-
25	1	14.7	17.3	33	4.98	56	1	-
40	1½	17.8	18.4	43	5.56	75	1	-
50	2	19.0	19.2	44	7.14	84	✓	-













### **Equal Tee**

### THREADED - Dimensions in millimeters

	Nominal	Length of T	hread (min)				Grades A	Available
DN								
15	1/2	10.9	13.6	33	4.09	38	✓	✓
20	3/4	12.7	13.9	38	4.32	46	✓	✓
25	1	14.7	17.3	44	4.98	56	✓	✓
40	1½	17.8	18.4	60	5.56	75	✓	-
50	2	19.0	19.2	64	7.14	84	1	1



## **Reducing Tees**

### THREADED - Dimensions in millimeters

Nom. P	ipe Size	Le	ength of T	hread (mi			Flow		Branch	Grades Available
					nch					
Flow	Branch									316L
3/4	1/2	12.7	13.9	10.9	13.6	38	4.32	46	38	<b>√</b>
1	1/2	14.7	17.3	10.9	13.6	44	4.98	56	38	<b>√</b>





### **Half Coupling**


### THREADED - Dimensions in millimeters

	Nominal	Length of T	hread (min)			Grades A	Available
DN					D		
6	1/8	6.4	6.7	32	16	-	✓
10	3/8	9.1	10.4	38	22	-	✓
15	1/2	10.9	13.6	48	28	-	✓
20	3/4	12.7	13.9	51	35	-	✓
25	1	14.7	17.3	60	44	-	✓
40	1½	17.8	18.4	79	64	-	✓











## **Full Coupling**

THREADED - Dimensions in millimeters

	Nominal	Length of T	hread (min)			Grades A	Available
DN					D		
6	1/8	6.4	6.7	32	16	-	✓
8	1/4	8.1	10.2	35	19	-	1
10	3/8	9.1	10.4	38	22	-	✓
15	1/2	10.9	13.6	48	28	<b>✓</b>	✓
20	3/4	12.7	13.9	51	35	<b>✓</b>	✓
25	1	14.7	17.3	60	44	<b>√</b>	✓
32	1¼	17.0	18.0	67	57	✓	-
40	1½	17.8	18.4	79	64	<b>√</b>	✓
50	2	19.0	19.2	86	76	✓	✓



### Union

THREADED - Dimensions in millimeters

Nom. Pipe Size	Pipe End (min) A	Wall (min) C	Water Way Bore D	Male Flange (min) F	Nut (min) G	Thrds / 25.4mm	Bearing (min) J	Length Assem. Nom. L	Clear Assem. Nut N	Grades Available	
											316L
1/2	27.7	3.73	17.86 17.07	3.68	3.68	14	1.50	49	58.4	-	1
3/4	33.5	3.91	23.01 21.39	4.06	4.06	11	1.68	56.9	66.0	1	1
1	41.4	4.55	28.98 27.74	4.57	4.45	11	1.85	62.0	78.7	1	1
1¼	50.5	4.85	37.69 35.36	5.33	5.21	10	2.13	71.1	94.0	-	1
1½	57.2	5.08	43.54 41.20	5.84	5.59	10	2.31	76.5	111.8	1	1
2	70.1	5.54	55.58 52.12	6.60	6.35	10	2.69	86.1	132.1	1	1





### Cap


THREADED - Dimensions in millimeters

	Nominal	Length of Thread (min)					Grades Available	
DN					D			
15	1/2	10.9	13.6	32	28	6.4	-	✓
20	3/4	12.7	13.9	37	35	6.4	-	✓
50	2	19.0	19.2	48	76	12.7	-	✓









Threads
Minimum 4 Full Threads
Engagement Class 2A/2B fit
ANSI B1:1





## **Hexagon Nipple**

THREADED - Dimensions in millimeters


	Nominal						Grades Available	
DN		A (Min)	W (Min)	E (Min)		C (Min)		
6	1/8	11	26	10	5	6	-	✓
8	1/4	15	36	15	8	6	-	✓
10	3/8	18	40	16	11	8	-	✓
15	1/2	22	48	20	14	8	-	✓
20	3/4	27	52	21	19	10	-	✓
25	1	35	60	25	24	10	-	✓
40	1½	50	68	26	38	16	-	✓
50	2	62	71	27	49	17	-	✓





## **Hexagon Plug**

THREADED - Dimensions in millimeters

	Nominal				Grades Available	
DN		A (Min)		H (Min)		316L
6	1/8	10	11	6	-	✓
8	1/4	11	16	6	-	1
10	3/8	13	18	8	-	✓
15	1/2	14	22	8	-	✓
20	3/4	16	27	10	-	✓
25	1	19	36	10	-	✓
40	1½	21	50	16	-	✓
50	2	22	65	18	-	✓









## Stainless Steel High Pressure Fittings



As one of the largest independent metal stockholders in the UK, we have a lot to offer our customers:

- An extensive inventory of Aluminium, Copper, Brass and bronze in all semi-finished forms
- A wide range of grades / alloys in all shapes and sizes
- A comprehensive processing service which includes polishing, coating, blanking and 'cut to length'
- A knowledgeable and dedicated workforce with nationwide coverage provided by our 18 Service Centres
- Reliable on-time delivery of orders

For further information, please contact your local Aalco Service Centre, or visit our website

# www.aalco.co.uk

Tel 01224 854810 e-mail aberdeen@aalco.co.uk

**AYLESBURY** Tel 01296 461700 e-mail aylesbury@aalco.co.uk

Tel 02890 838838 e-mail belfast@aalco.co.uk

Tel 0121 585 3600 e-mail birmingham@aalco.co.uk

Tel 01291 638638 e-mail chepstow@aalco.co.uk

Tel 01269 842044 e-mail dyfed@aalco.co.uk

Tel 01268 884200 e-mail essex@aalco.co.uk

Tel 0141 646 3200 e-mail glasgow@aalco.co.uk

Tel 01482 626262 e-mail hull@aalco.co.uk

Tel 0113 276 3300 e-mail leeds@aalco.co.uk

Tel 0151 207 3551 e-mail liverpool@aalco.co.uk

Tel 01204 863456 e-mail manchester@aalco.co.uk

Tel 0191 4911133 e-mail newcastle@aalco.co.uk

Tel 01603 787878 e-mail norwich@aalco.co.uk

Tel 0115 988 2600 e-mail nottingham@aalco.co.uk

Tel 02380 875200 e-mail southampton@aalco.co.uk

Tel 01782 375700 e-mail stoke@aalco.co.uk

Tel 01322 610900 e-mail swanley@aalco.co.uk